

Picture may differ from original product




SX Rubber Series

Wheel Diameter × Wheel Width 100 x 35mm

YJ-12040304156171 Copy model no.

Wheel Diameter(D)	Load Capacity (Dynamic)	Wheel Bearing
100mm	**150kgs**	**Ball Bearing**

- Made of High-Quality Resilient Rubber.
- Features excellent handling comfort, good Floor Surface Preservation, and Shock-Absorbing.
- Excellent resistance to chemicals, solvents, and corrosion.
- Suitable for industrial and heavy-duty wheels.
- Rubber, black, with a curved rim and V-patterned surface.
- Increases grip and effectively improves slip resistance.
- Wheel Center: cast iron core
- Outer packaging: rubber
- Bearing: Ball bearing

Product descriptions are for reference only. The actual product shall prevail.

Product Data Sheet | 3D Drawing Request

3D drawings are for members only. Please log in to download.

Product Data Sheet

Metric | Imperial

Wheel Diameter(D)	**100mm**	Wheel Width(T2)	**35mm**
Wheel Bearing	**Ball Bearing**	Axle Bore(d)	**15mm**
Axle Bore(S)	**mm**	Bearing Bore Depth(t)	
Hardness Of Tread	**85±5° Shore A**	Load Capacity (Dynamic)	**150kgs**
Load Capacity (Static)	**225kgs**	Temperature	**-20°C to +120°C**
Electrical Conductivity	**N/A**	Anti-Static	**N/A**
Weight	**0.55kgs**	Standard	**ISO22883**

* For any deviation between metric and imperial spec, please refer to the metric spec.

Performance

Rolling Smoothness
Max. 5 points Score: 3

Quiet Operation
Max. 5 points Score: 4

Floor Surface Preservation
Max. 5 points Score: 4

Downloads

PDF **1203-EN-YJ2026110303.pdf**
Product Data Sheet

3D **1203-CN-YJ2026110303-d261103152638.rar**
3D drawings are for members only. Please log in to download.

© 2026 DERSHENG CO., LTD. All rights reserved.