

Picture may differ from original product




SX Rubber Series

# Wheel Diameter × Wheel Width 174.5 x 35mm

YJ-12040307156301 Copy model no.

| Wheel Diameter(D) | Load Capacity (Dynamic) | Wheel Bearing |
|---|---|---|
| **174.5mm** | **200kgs** | **Without Bearing** |

- Made of High-Quality Resilient Rubber
- Features excellent handling comfort, good Floor Surface Preservation, and Shock-Absorbing.
- Excellent resistance to chemicals, solvents, and corrosion.
- Suitable for industrial and heavy-duty wheels.
- Rubber, Black, Curved Surface, V-pattern.
- Increases grip and effectively improves slip resistance.
- Wheel Center: cast iron core
- Outer packaging: rubber
- Bearings: —

Product descriptions are for reference only. The actual product shall prevail.

Product Data Sheet | 3D Drawing Request

3D drawings are for members only. Please log in to download.

## Product Data Sheet

Metric | Imperial

| | | | |
|---|---|---|---|
| Wheel Diameter(D) | **174.5mm** | Wheel Width(T2) | **35mm** |
| Wheel Bearing | **Without Bearing** | Axle Bore(d) | |
| Axle Bore(S) | **20.5mm** | Bearing Bore Depth(t) | |
| Hub Lenth(T1) | **37mm** | Hardness Of Tread | **85±5° Shore A** |
| Load Capacity (Dynamic) | **200kgs** | Load Capacity (Static) | **300kgs** |
| Temperature | **-20°C to +120°C** | Electrical Conductivity | **N/A** |
| Anti-Static | **N/A** | Weight | **1.54kgs** |
| Standard | **ISO22883** | | |

* For any deviation between metric and imperial spec, please refer to the metric spec.

## Performance

**Rolling Smoothness**
Max. 5 points Score: 3

**Quiet Operation**
Max. 5 points Score: 4

**Floor Surface Preservation**
Max. 5 points Score: 4

## Downloads

PDF **1203-EN-YJ2026111002.pdf**
Product Data Sheet

3D **1203-CN-YJ2026111002-d261110091015.rar**
3D drawings are for members only. Please log in to download.



© 2026 DERSHENG CO., LTD. All rights reserved.