

Picture may differ from original product




AHPU Series

Wheel Diameter × Wheel Width 130 x 39mm

YJ-12039605130201 Copy model no.

Wheel Diameter（D）	Tread Pattern	Load Capacity at 6 km/h
130mm	—	**170kgs**

- Excellent mechanical properties and abrasion resistance
- Excellent chemical resistance、Resistance to corrosive substances
- Suitable for forklifts、Electric stackers、AGV automation and floor-scrubber applications
- HPU，Dark gray，Machined random-pattern surface
- Increases floor traction，Effectively improves slip resistance
- Inner bushing：Aluminum core

Product descriptions are for reference only. The actual product shall prevail.

Product Data Sheet | 3D Drawing Request

3D drawings are for members only. Please log in to download.

Product Data Sheet

Metric | Imperial

Wheel Diameter（D）	**130mm**	Wheel Width（T2）	**39mm**
Wheel installation — Hub Lenth (T1)	**50mm**	Wheel center-bore diameter (d)	**102mm**
Wheel Mounting Bolt Hole PCD Diameter	**3.5mm**	Wheel Mounting Bolt Hole PCD	**97mm**
# Of Wheel mounting bolt boles	**6**	Wheel mounting bolt hole (M)	**4**
Number of wheel mounting bolt holes	**3**	Load Capacity (Static)	**300kgs**
Load Capacity at 4 km/h	**200kgs**	Load Capacity at 6 km/h	**170kgs**
Load Capacity at 10 km/h	**140kgs**	Load Capacity at 16 km/h	**80kgs**
Hardness Of Tread	**80±5° Shore A**	Temperature	**-20°C to +70°C**
Tread Pattern	—	Wheel centre/ rim	
Non-Marking	**Y**	Conductive	**N/A**
Anti	**N/A**	Weight	**0.42kgs**
Standard	**ISO22883**		

* For any deviation between metric and imperial spec, please refer to the metric spec.

Performance

Rolling Smoothness
Max. 5 points Score: 5

Quiet Operation
Max. 5 points Score: 4

Floor Surface Preservation
Max. 5 points Score: 5

Downloads

PDF **YJ-120396051302012.pdf**
Product Data Sheet

3D **12039605130201.rar**
3D drawings are for members only. Please log in to download.

© 2026 DERSHENG CO., LTD. All rights reserved.